Washer extractors

W3130H, W3180H, W3240H

Features and benefits

- · High extraction force for efficient dewatering
- Low water consumption, up to 12 liter/kg dry linen (60°C without pre-wash). Depending on application
- · Available with two types of electronic controls:
 - Exacta Control(R) with up to 28 fixed wash program combinations. Some parameters programmable
 - Clarus Control fully programmable, up to 192 programs
- · Large door opening for easy loading/unloading
- · Low noise level, for pleasant working environment
- Stainless and galvanized steel in all vital parts for high degree of rust protection
- · Prepared for manual or automatic detergent supply
- Stainless steel front panel and powder painted side panels

Main options

- · Stainless steel side panels
- Payment systems: Single System card-reader, coin-meter or central payment system (Exacta Control(R))
- Dual drain valves for water re-use (Clarus Control)
- Special electrical heating elements for heavy soiled applications (e.g. floor mops) (W3130H only)




Main specifications				W3130H		W3180H		W3240H	
Rated capacity, filling factor 1:10		kg/lb	13/30		18/40		24/55		
	filling factor 1:13		kg/lb	10	/22	13.8	3/30	18.5	5/40
Drum,	volume		litre	13	30	18	80	24	10
	diameter		ø mm	65	50	72	.5	79	95
Extraction		rpm	980		930		890		
G-factor	G-factor G-factor			350		350		350	
Heating alternat	Heating alternatives electricity		kW	13		18		23	
		steam		>	(×)	(
		non-heated		>	(X		X	
Consumption d	Consumption data "Normal 60°C" *			El	Steam	El	Steam	El	Steam
Total time			min	47	**	47	**	45	**
	Water consumption (cold/hot)			133/24	133/24	187/33	187/33	227/52	227/52
Energy consumption (motor/heating)*			kWh	0.3/0.9	0.3	0.45/1.25	0.45	0.6/1.7	0.6
Steam consumption		kg	-	1.3	-	1.9	-	2.5	
 Water temperature 15°C cold water and 65°C hot water. Depending on steam pressure. 									


Certified in accordance with ISO 9001 and ISO 14001 and approved IP 24D.



Electrical	connections*		W3130H W3180H		W3240H		
Heating	Voltage						
EI.	230V 3 AC 50 Hz	kW(A)	12.5(35)	17.4(50)	22.2(63)		
	240V 3AC 60 Hz 400V 3N AC 50 Hz	kW(A) kW(A)	12.5(35) 12.5(20)	18.9(50) 17.6(35)	24.1(63) 22.4(35)		
Ctoom					, ,		
Steam	230V 1AC 60 Hz 240V 1AC 60 Hz	kW(A) kW(A)	1.7(10) 1.7(10)	2.4(16) 2.4(16)	2.6(16) 2.6(16)		
1	d 230V 1AC 50 Hz	kW(A)	1.7(10)	2.4(16)	2.6(16)		
Water and	d steam connectio	n	, ,	, ,	, ,		
Water valv	res	DN	20	20	20		
Water pressure ki			150-400	150-400	150-400		
	Capacity at 300 kPa		27	60	60		
	Drain valve Draining capacity		75 150	75 150	75 150		
	raining capacity I/m team valve E		15	15	15		
Steam pre		kPa	300-600	300-600	300-600		
	ergent supplies		5	5	5		
Floor requ							
Max floor	of the dynamic for load at extraction	ce Hz kN	16.4 3.0 <u>+</u> 0.5	15.5 3.9 <u>+</u> 1.0	14.8 4.5 <u>+</u> 1.0		
Sound lev	rels						
	ound level	dB(A)	73	80	80		
Heat emis							
	lled power, max		5	5	5		
Shipping	data						
Weight		net, kg	267 284	356 376	429 448		
Shipping volume		crated, kg m³	1.27	1.64	1.79		
Accessor	ies						
Steel base	e frame		Х	Х	Х		
Water re-use tank (Clarus Control)			х	х	Х		
Hose connection kits for water or steam			Х	Х	X		
Dimensio	ns in mm						
A Width			910	970	1020		
B Depth			785	870	915		
C Height			1325	1410	1445		
D E			435 825	470 910	500 955		
F			1035	1120	1155		
G			125 1245	115	100		
H				1330	1360		
I K			215 1225	230 1290	215 1320		
L			300	315	300		
M			-	395	380		
N O			100 305	100 335	100 360		
P			455	485	510		
	al connections	6		ly connections	5		
2 Cold wa		7	Control panel				
3 Hot water 8 4 Steam connection 9			Soap box Door opening ø395 (W3130H),				
5 Drain	33.110011011	,		0H,W3240H)	, , , , , , , , , , , , , , , , , , , ,		

⁹ C C 5377





Electrolux

ELECTROLUX LAUNDRY SYSTEMS

Lundtoftegaardsvej 93A, DK-2800 Lyngby, Denmark Telephone: +45 4526 4800. Telefax: +45 4526 4801 Internet: www.electrolux.com/laundrysystems E-mail: els.info@electrolux.com

 $^{^{\}star}\,$ Other voltages available, see installation manual.